

**Harvatek Surface Mount CHIP LED Data Sheet
HT-191NB5-K589**

Official Product	HT Part No. HT-191NB5-K589	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0	Page 1/13

DISCLAIMER..... 3

PRODUCT SPECIFICATIONS 4

ATTENTION: ELECTROSTATIC DISCHARGE (ESD) PROTECTION4

LABEL SPECIFICATIONS 5

PRODUCT FEATURES 7

ELECTRO-OPTICAL CHARACTERISTICS.....7

PACKAGE OUTLINE DIMENSION AND RECOMMENDED SOLDERING PATTERN FOR REFLOW

SOLDERING.....7

ABSOLUTE MAXIMUM RATINGS7

CHARACTERISTICS OF HT-191NBXXXX.....8

PACKAGING 9

TAPE DIMENSION9

REEL DIMENSION.....10

PACKING.....10

DRY PACK.....11

PRECAUTIONS.....11

REFLOW SOLDERING..... 12

REWORKING.....12

CLEANING.....12

RELIABILITY TEST.....13

Official Product	HT Part No. HT-191NB5-K589	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0	Page 2/13

DISCLAIMER

HARVATEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. HARVATEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

LIFE SUPPORT POLICY

HARVATEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of HARVATEK or HARVATEK INTERNATIONAL. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.

2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Official Product	HT Part No. HT-191NB5-K589	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0	Page 3/13

Product Specifications

	Specification	Material	Quantity
Iv	18-45 mcd @5mA/ Ta= 25 ^o ;Tolerance: ± 10%		
λ _D	465-475nm @5mA/ Ta= 25 ^o C;Tolerance: ± 0.5nm		
Vf	2.55-3.15V @5mA/ Ta= 25 ^o C ;Tolerance: ± 0.05V		
Ir	< 100 μA @ V _R = 5 V		
Resin	Milky White	Epoxy resin	
Carrier tape	EIA 481-1A specs	Conductive black tape	4000pcs per reel
Reel	EIA 481-1A specs	Conductive black	
Label	HT standard	Paper	
Packing bag	220x240mm	Aluminum laminated bag/ no-zipper	One reel per bag
Carton	HT standard	Paper	Non-specified

Others:

Each immediate box consists of 5 reels. The 5 reels may not necessarily have the same lot number or the same bin combinations of Iv, λ_D and Vf. Each reel has a label identifying its specification; the immediate box consists of a product label as well.

ATTENTION: Electrostatic Discharge (ESD) protection









The symbol to the left denotes that ESD precaution is needed. ESD protection for GaP and AlGaAs based chips is necessary even though they are relatively safe in the presence of low static-electric discharge. Parts built with AlInGaP, GaN, or/and InGaN based chips are **STATIC SENSITIVE devices**. ESD precaution must be taken during design and assembly.

If manual work or processing is needed, please ensure the device is adequately protected from ESD during the process.

Official Product	HT Part No. HT-191NB5-K589	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0
			Page 4/13

Label Specifications

HARVATEK 		DATE: dd/mm/yyyy	
CUSTOMER P/N:			
HARVATEK P/N:		QTY:	PCS
LOT NO:		QC:	
IV BIN:		VF:	
COLOR BIN:			

■ Customer P/N: To Be Defined

■ Harvatek P/N:

H T - 1 9 1 NB5-K589

Series Name	Emitting Color
HT-191 1.6(L)x0.8(W)x0.6(H) mm	NB5: Blue Kxxx Product code

■ Lot No.:

1 2 3 4 5 6 7 8 9 10
P 1 2 2 3 0 A - D T

Code 1	Code 2	Code 3	Code 4, 5	Code 6, 7	Code 9	Code 10
	Mfg. Year	Mfg. Month	Mfg. Date	Lots	Resin Color	Packaging
Internal Tracing Code	Z: 2000 1: 2001 2: 2002 3: 2003	1: Jan. 2: Feb. 9: Sep. A: Oct. B: Nov. C: Dec.	1~31/ (30)	01~99, A,B,C...	D: Milky White	T: Tape & Reel

Official Product	HT Part No. HT-191NB5-K589	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0 Page 5/13

■ Luminous Intensity (Iv) Bin:

Color	Bin Code	Spec. Range
NB	M	18-28 mcd
	N	28-45 mcd

■ Dominant Wavelength (λ_D) Bin:

Color	Bin Code	Spec. Range
NB	B	465-470 nm
	C	470-475 nm

■ Forward Voltage (Vf) Bin:

Color	Bin Code	Spec. Range
NB	G2T	2.55-2.65 V
	G3T	2.65-2.75 V
	G4T	2.75-2.85 V
	H1T	2.85-2.95 V
	H2T	2.95-3.05 V
	H3T	3.05-3.15 V

Official Product	HT Part No. HT-191NB5-K589	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0
			Page 6/13

Product Features

Electro-Optical Characteristics

(I_F @ 5mA, T_a 25 °C)

Code for parts	Lighting Color		V_F (V)		λ (nm)			I_v (mcd)
			typ	max	λ_D	λ_P	$\Delta \lambda$	Min
HT-191NB5-XXX	Blue	InGaN	2.8	3.15	472	470	40	18

Package Outline Dimension and Recommended Soldering Pattern for Reflow Soldering

Unit: mm Tolerance: +/-0.1

Outline Dim.	Soldering Pattern
<p>Soldering terminals may shift in the x, y direction.</p>	

Absolute Maximum Ratings




(T_a 25 °C)

Series	P_d (mW)	I_F (mA)	I_{FP} (mA)	V_R (V)	I_R (uA)	T_{OP} (°C)	T_{ST} (°C)
191NBx	78	20	100	5	<100@ $V_R = 5$	-30~+80	-40~+85

** Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width



Official Product	HT Part No. HT-191NB5-K589	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0	Page 7/13

Characteristics of HT-191NBxxxx




Directive Characteristics

Directive Characteristics




Official Product	HT Part No. HT-191NB5-K589	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0
			Page 8/13

Packaging
Tape Dimension




Part No.	Dim. A	Dim. B	Dim. C	Q'ty/Reel
HT-191	1.8±0.10	0.95±0.10	0.75±0.10	4K

Unit: mm




Official Product	HT Part No. HT-191NB5-K589	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0	Page 9/13

Reel Dimension



Packing



5 boxes per carton is available depending on shipment quantity.


Official Product	HT Part No. HT-191NB5-K589	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0
			Page 10/13

Dry Pack

All SMD optical devices are **MOISTURE SENSITIVE**. Avoid exposure to moisture at all times during transportation or storage. Every reel is packaged in a moisture protected anti-static bag. Each bag is properly sealed prior to shipment.

Upon request, a humidity indicator will be included in the moisture protected anti-static bag prior to shipment.

The packaging sequence is as follows:



PRECAUTIONS

1. Avoid exposure to moisture at all times during transportation or storage.
2. Anti-Static precaution must be taken when handling GaN, InGaN, and AlInGaP products.
3. It is suggested to connect the unit with a current limiting resistor of the proper size. Avoid applying a reverse voltage beyond the specified limit.
4. Avoid operation beyond the limits as specified by the absolute maximum ratings.
5. Avoid direct contact with the surface through which the LED emits light.
6. If possible, assemble the unit in a clean room or dust-free environment.


Official Product	HT Part No. HT-191NB5-K589	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0	Page 11/13

Reflow Soldering

Recommend soldering paste specifications:

1. Operating temp.: Above 220 °C ,60 sec.
2. Peak temp.:260 °CMax.,10sec Max.
3. Never attempt next process until the component is cooled down to room temperature after reflow.
4. The recommended reflow soldering profile (measured on the surface of the LED terminal) is as following:

Lead-free Solder Profile



Reworking

- Rework should be completed within 5 seconds under 260 °C.
- The iron tip must not come in contact with the copper foil.
- Twin-head type is preferred.

Cleaning

Following are cleaning procedures after soldering:

- An alcohol-based solvent such as isopropyl alcohol (IPA) is recommended.
- Temperature x Time should be 50°C x 30sec. or <30°C x 3min
- Ultrasonic cleaning: < 15W/ bath; bath volume ≤ 1liter
- Curing: 100 °C max, <3min

Official Product	HT Part No. HT-191NB5-K589	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0	Page 12/13

Cautions of Pick and Place

- Avoid stress on the resin at elevated temperature.
- Avoid rubbing or scraping the resin by any object.
- Electric-static may cause damage to the component. Please ensure that the equipment is properly grounded. Use of an ionizer fan is recommended.

Reliability Test

Item	Frequency/ lots/ samples/ failures	Standards Reference	Conditions
Precondition	For all reliability monitoring tests according to JEDEC Level 2	J-STD-020	1.) Baking at 85°C for 24hrs 2.) Moisture storage at 85°C/ 60% R.H. for 168hrs
Solder ability	1Q/ 1/ 22/ 0	JESD22-B102-B And CNS-5068	Accelerated aging 155°C/ 24hrs Tinning speed: 2.5±0.5cm/s Tinning: A: 215°C/ 3±1s or B: 260°C/ 10±1s
Resistance to soldering heat		CNS-5067	Dipping soldering terminal only Soldering bath temperature A: 260±/-5°C; 10±/-1s B: 350±/-10°C; 3±/-0.5s
Operating life test	1Q/ 1/ 40/ 0	CNS-11829	1.) Precondition: 85°C baking for 24hrs 85°C/ 60%R.H. for 168hrs 2.) T _{amb} 25°C; I _F =20mA; duration 1000hrs
High humidity, high temperature bias	1Q/ 1/ 45/ 0	JESD-A101-B	T _{amb} : 85°C Humidity: 85% R.H., I _F =5mA Duration: 1000hrs
High temperature bias	1Q/ 1/ 20/ 0	HT specs.	T _{amb} : 55°C I _F =20mA Duration: 1000hrs
Pulse life test	1Q/ 1/ 40/ 0		T _{amb} 25°C, I _F =20mA, I _p =100mA, Duty cycle=0.125 (tp=125 μs, T=1sec) Duration 500hrs)
Temperature cycle	1Q/ 1/ 76/ 0	JESD-A104-A IEC 68-2-14, Nb	A cycle: -40 degree C 15min; +85 degree C 15min Thermal steady within 5 min.. 300 cycles 2 chamber/ Air-to-air type
High humidity storage test	1Q/ 1/ 40/ 0	CNS-6117	60±3°C 90+5/-10% R.H. for 500hrs
High temperature storage test	1Q/ 1/ 40/ 0	CNS-554	100±10°C for 500hrs
Low temperature storage test	1Q/ 1/ 40/ 0	CNS-6118	-40±5°C for 500hrs

Official Product	HT Part No. HT-191NB5-K589	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	HDS-191-K589
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		2008/2/14	Version 1.0 Page 13/13